



# NS SERIES BRIDGE LIGHT

*Medium Intensity LED Bridge Light  
4 NM at 0.74T | 4.8 NM at 0.85T*



## OVERVIEW

The NS SERIES BRIDGE LIGHT is the new standard in LED bridge lighting for marking channels, obstructions and safe passage of bridges over navigable waters throughout the USA. The LEDs are on a protected metal core PCB for maximum useful life with flexible electronic configuration. Use as Green Channel Center, 180° Red Channel Margin, and White Channel Main lights.

## KEY FEATURES

- AC/DC input: 120-240 VAC or 12-24 VDC input options
- Sectored lens: 180° form fitting sectored lens (Optional)
- Zero condensation: designed specifically for inversion with strategically placed vent
- Rugged, weather-resistant construction materials: High impact resistant polycarbonate for ice, ultraviolet exposure, salt air and seawater spray at a wide range of ambient temperatures
- High intensity, energy efficient fan beam LED array: Maximum visible range up to 4NM at 0.74T
- IR Remote: Powering on & off, set / retrieve configuration parameters such as flash pattern, effective intensity, day/night control, etc.
- USCG approved colors: Single color LED engine - Red, Green or White
- Longevity - Estimated average service life of 10 years

## PERFORMANCE FEATURES

- Intensity control: Effective lantern intensity set on Schmidt-Clausen method
- Day/Night transition level settings: Programmable for active at all times or only after sunset. Day / Night level settings (sunset / sunrise transition) can be field programmed
- Calendar control - Programmable season on/off date
- Input protection - Lantern power input is reversed polarity protected for field repair
- Storage mode - Automatic storage mode with adjustable automatic wake up
- Programmable sleep and test modes
- Dynamic compensation circuitry for the candela low output, based on internal temperature, LED flash duration and LED color, to always keep the same programmed output intensity

## OPTIONAL FEATURES

- External I/O port: Allows connection to an external monitoring device or for hardwired synchronization to other lanterns

## SWING ARM ASSEMBLIES

- Customized to meet customer requirements
- Available in aluminum, anodized aluminum or galvanized steel
- Includes locking mechanism for easy maintenance
- Includes customer choice of NEMA 4X junction boxes or rigid metal conduit boxes

## PHYSICAL SPECIFICATIONS

Width	242mm / 9.53"
Depth	242mm / 9.53"
Height	214 mm / 8.42 in
Weight	1.18 kg / 2.6 lb
Operating Temperature Range	-30°C to +50°C
Operating Humidity	100
IP Rating	IP68*
Body Material	UV stabilized polycarbonate
Lens Material	Acrylic
Mounting	3 - 4 hole, Ø 200mm

## STANDARDS

EMI/EMC	EN55015:2013 radiated and conducted emissions* EN61547:2009 Immunity FCC 47 CFR Section 15 Class A*
Optical Test	IALA Recommendation E-122 (2001) and E-200-3 Part 3 (2008)
Colour	IALA Recommendation E-200-1 Part 1
Daylight	IALA Recommendation 1038
Power Supply	IEC60945 Section 7 normal and peak voltage, and reverse polarity protection
Ingress	IP68 to IEC60529
Shock	MIL-STD-202G Method 213B Cond H*
Vibrating	MIL-STD-202G Method 204D Cond B*
Immersion	MIL-STD-202G Method 104A Cond B withstands immersion to 1m depth*
Ice	Standard


## OPTICAL CHARACTERISTICS

LED Color	White	Red	Green
Light Source	12 White LEDs	12 Red LEDs	12 Green LEDs
Visible Range (NM) <sup>1</sup>	4	4	4
Effective Intensity Range	10 - 151 <sup>3</sup>	10 - 151 <sup>3</sup>	10 - 151 <sup>3</sup>
Horizontal Divergence	180° or 360°	180° or 360°	180° or 360°
Vertical Divergence (at 50% intensity)	10°	10°	10°
Peak Intensity	32	32	32

<sup>1</sup>Visible range based on IALA standards at atmospheric transitivity of 0.74

<sup>2</sup> Effective intensity computed from Blondel Rey method

<sup>3</sup> Maximum Effective Intensity limited by ambient temperature and flash length



IALA Recommendation O-113 and USCG 33 CFR 118 Approved. Lights required by the regulations shall be of sufficient candlepower as to be visible against the background lighting at a distance of at least 2,000 yards on 90 percent of the nights of the year. They are located as prescribed, with colors and arcs of visibility as specified.



\*All values are subject to change without notice.

**Pharos Marine Automatic Power, Inc.**  
Houston, TX - USA  
sales@automaticpower.com  
Phone: +1-713-228-5208

**Pharos Marine Automatic Power**  
Gray, LA - USA  
rleblanc@automaticpower.com  
Phone: +1-985-223-8700

**Pharos Marine Automatic Power, Ltd.**  
London, UK  
sales@pharosmarine.com  
Phone: +44-20-8538-

**AB Pharos Marine Pte.**  
Singapore  
sales@pharos-api.com  
Phone: +65-6747-9325